change-bar

The change bar can be arranged to right and left of the text.
This property determines where, relative to the column areas, the change bars will occur.

XML format is being adopted by corporations at an increasing rate as the preferred format for data, including order data, exchanged within an organization, as well as between corporations.

XML format is being adopted by corporations at an increasing rate as the preferred format for data, including order data, exchanged within an organization, as well as between corporations.

XML format is being adopted by corporations at an increasing rate as the preferred format for data, including order data, exchanged within an organization, as well as between corporations.

XML format is being adopted by corporations at an increasing rate as the preferred format for data, including order data, exchanged within an organization, as well as between corporations.

XML format is being adopted by corporations at an increasing rate as the preferred format for data, including order data, exchanged within an organization, as well as between corporations.

XML format is being adopted by corporations at an increasing rate as the preferred format for data, including order data, exchanged within an organization, as well as between corporations.

XML format is being adopted by corporations at an increasing rate as the preferred format for data, including order data, exchanged within an organizationas well as between corporations.

XML format is being adopted by corporations at an increasing rate as the preferred format for data, including order data, exchanged within an organization, as well as between corporations.

XML format is being adopted by corporations at an increasing rate as the preferred format for data, including order data, exchanged within an organization, as well as between corporations.

XML format is being adopted by corporations at an increasing rate as the preferred format for data, including order data, exchanged within an organization, as well as between corporations.

A change bar specifies starting by "fo:change-bar-begin",
and specifies the end using "fo:change-bar-end".
In order to make "end" match with "begin", class names
are specified to be "fo:change-bar-begin" and "fo:change-
bar-end" using "change-bar-class."